

TRANCE X E+ 1



www.georgesbikeshop.com.au

SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 800, EnergyPak Plus 250Wh range extender compatible
FRAME	
SIZES	Cold Night
COLOURS	Cold Night/Cobalt
FRAME	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
FORK	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip Damper, Boost 110x15QR, e-optimized
SHOCK	Fox Float X Performance, EVOL Large Volume sleeve, 2-Pos Lever, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail
GRIPS	Giant New trail grip Half-waffle/single lock-on
STEM	Giant Contact SL 35
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm, M: 140-170mm travel / 30.9 x 499mm, L: 170-200mm travel / 30.9 x 525mm, XL: 170-200mm travel / 30.9 x 525mm
SADDLE	Giant Romero E
PEDALS	Flat pedal
DRIVETRAIN	
SHIFTERS	Shimano Deore XT
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore XT, 12-speed, Shadow+
BRAKES	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm
BRAKE LEVERS	Shimano Deore XT, I-spec EV
CASSETTE	Shimano CS-M7100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wave 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant AM 29"
HUBS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimized
TIRES	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers)
ACCESSORIES	
LOCK	Torx 25 Battery Lock with built-in Torque limiter

Price: \$9,499 RRP

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		425		450		475	
Seat Tube Angle	76.0°	76.7°	76.0°	76.7°	76.0°	76.7°	76.0°	76.7°
Top Tube Length (mm)	577	575	610	605	637	635	667	665
Head Tube Length (mm)	95		100		110		120	
Head Tube Angle	65.7°	66.5°	65.8°	66.5°	65.8°	66.5°	65.8°	66.5°
Fork Rake (mm)	44		44		44		44	
Trail (mm)	117	122.4	117	122.4	117	122.4	117	122.4
Wheelbase (mm)	1205	1206	1239	1237	1268	1269	1300	1301
Chain Stay Length (mm)	473	473	473	473	473	473	473	473
Bottom Bracket Drop (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	611	605	621	614	630	624
Reach (mm)	439	447	457	462	482	489	510	517
Stand Over Height (mm)	783	789	775	784	763	770	775	782
Stem Length (mm)	40		50		50		60	
Crank Length (mm)	160		165		165		170	
Wheel Size	29"		29"		29"		29"	

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.