



## SPECS

| FRAME            |   |
|------------------|---|
| SIZES            | S, M, L, XL   |
| COLOURS          | Pyrite Brown, Cold Night  |
| FRAME            | ALUXX SL-grade aluminium, 12x148mm thru-axle  |
| FORK             | Giant Crest 34 RCL, 130mm, 44mm offset, Boost 15x110  |
| SHOCK            | N/A   |
| COMPONENTS       |   |
| HANDLEBAR        | Giant Contact TR35, 35mm  |
| GRIPS            | Giant Sole-O  |
| STEM             | Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm   |
| SEATPOST         | Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm<br>M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 440mm XL:<br>170mm travel / 30.9 x 455mm |
| SADDLE           | Giant Romero  |
| PEDALS           | N/A   |
| DRIVETRAIN       |   |
| SHIFTERS         | Shimano CUES SL-6000-10R, 1x10  |
| FRONT DERAILLEUR | N/A   |
| REAR DERAILLEUR  | Shimano CUES, U6000, Shadow+  |
| BRAKES           | Tektro HDM 275, hydraulic, Tektro rotors [F]180mm, [R]180mm   |
| BRAKE LEVERS     | Tektro HDM 275  |
| CASSETTE         | Shimano CUES, CS-LG300, 11x48   |
| CHAIN            | Shimano CUES LG500  |
| CRANKSET         | Shimano CUES FC-U6000-1, 30t S:170mm, M:170mm, L:170mm,<br>XL:170mm   |
| BOTTOM BRACKET   | Shimano, threaded   |

| WHEELS |   |
|--------|---|
| RIMS   | Giant AM 29, tubeless ready sleeve-joint rim, 30mm inner width                              |
| HUBS   | Alloy, sealed   |
| SPOKES | Stainless   |
| TIRES  | [F] Maxxis Minion DHF, 29x2.5 WT, EXO/TR[R] Maxxis Aggressor, 29x2.5<br>WT, foldable, EXO/T |
| EXTRAS | Tubeless prepared, 2.5" max tyre size, 32t max chainring size                               |

**Price: \$1,899.00**

## GEOMETRY

| FRAME                          | S     | M     | L     | XL    |
|--------------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm)          | 380   | 430   | 465   | 495   |
| Seat Post Insertion Depth (mm) | 300   | 200   | 235   | 285   |
| Seat Tube Angle                | 75.0° | 75.0° | 75.0° | 75.0° |
| Top Tube Length (mm)           | 592   | 612   | 639   | 662   |
| Head Tube Length (mm)          | 95    | 95    | 105   | 115   |
| Head Tube Angle                | 66.0° | 66.0° | 66.0° | 66.0° |
| Fork Rake (mm)                 | 44    | 44    | 44    | 44    |
| Trail (mm)                     | 122   | 122   | 122   | 122   |
| Wheelbase (mm)                 | 1157  | 1177  | 1206  | 1230  |
| Chain Stay Length (mm)         | 438   | 438   | 438   | 438   |
| Bottom Bracket Drop (mm)       | 60    | 60    | 60    | 60    |
| Stack (mm)                     | 622   | 622   | 631   | 640   |
| Reach (mm)                     | 425   | 445   | 470   | 490   |
| Stand Over Height (mm)         | 727   | 746   | 764   | 791   |
| Stem Length (mm)               | 40    | 40    | 50    | 50    |
| Crank Length (mm)              | 165   | 170   | 170   | 170   |
| Wheel Size                     | 29"   | 29"   | 29"   | 29"   |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.