

TRANCE ADVANCED 29 0



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Shoreline/Sea Sparkle/Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, UDH hanger, 12x148mm thru-axle, 55mm Chainline
FORK	Fox 34 Factory, 130mm, GRIP 2, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
SHOCK	Fox Float X Factory, 2 position lever with LSC adjust, Trunnion, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR Integrated, composite, 35mm
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SLR Trail, integrated, 40/45/50mm Reach, 7/9 degree Sweep Adjust System
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XO Eagle T-Type AXS
BRAKES	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XO, T-Type 10x52
CHAIN	SRAM XO T-Type
CRANKSET	SRAM XO T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM, press fit

WHEELS	
RIMS	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
HUBS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRAS	Tubeless prepared, 2.6" max tyre size, 34t max chainring size

Price: \$9,999.00

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	420	430	465	496				
Seat Post Insertion Depth (mm)	290	300	335	366				
Seat Tube Angle	77.2° 78.0°	76.3° 77.0°	76.3° 77.0°	76.3° 77.0°				
Top Tube Length (mm)	561 559	599 597	626 624	663 661				
Head Tube Length (mm)	100	110	120	130				
Head Tube Angle	65.4° 66.2°	65.5° 66.2°	65.5° 66.2°	65.5° 66.2°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	126 120	126 120	126 120	126 120				
Wheelbase (mm)	1166 1165	1195 1194	1124 1123	1263 1262				
Chain Stay Length (mm)	439 437	439 437	439 437	439 437				
Bottom Bracket Drop (mm)	45 35	45 35	45 35	45 35				
Stack (mm)	610 604	619 613	628 622	637 631				
Reach (mm)	422 431	447 456	472 480	507 515				
Stand Over Height (mm)	729 737	723 732	746 755	751 760				
Stem Length (mm)	40	40	50	50				
Crank Length (mm)	165	170	170	170				
Wheel Size	29"	29"	29"	29"				

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.