



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Smoke Metal
FRAME	ALUXX SL-Grade Aluminium front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage
FORK	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX M-7100, I-Spec EV, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX M-7100, Shadow +
BRAKES	Shimano BR-MT520, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore BL-MT501
CASSETTE	Shimano SLX M7100, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano Press Fit

WHEELS	
RIMS	Giant TRA WheelSystem, 6069 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAS	Tubeless prepared, 2.5" max tyre size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Price: \$5,499.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8° 77.2° 77.5°			76.8° 77.2° 77.5°			76.8° 77.2° 77.5°			76.8° 77.2° 77.5°		
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 65.1°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3	128.5
Wheelbase (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	1279
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Stand Over Height (mm)	732	737	742	746	750	755	763	768	773	781	758	790
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are